



SAFE EYE

Single Door Magnetic Lock (LED & Time)



Advantage:

- Dual Voltage 12 or 24 VDC(optional).
- The Standard Voltage is 12VDC when Finished.
- MOV Provides Reverse Current Protection.
- Suitable For Wooden Door,Glass Door,Metal Door,Fireproof Door.
- LED Indicates the Door Status.
- Lock Status sensor(NO/NC/COM).
- Time: 0/3/6/9sec.
- Anti-Residual Magnetism Designed.
- High Strength Material,Anodized Aluminum Housing.
- Design without Mechanical Failure.
- Increase the holding Force,Dual Insulative Housing

Technical Parameter

Model.NO	SA-500NT(LED)
Size	265Lx73Wx41H(mm)
Armature Plate Dimension	185Lx60Wx13.2H(mm)
Holding Force	500kg(1200Lbs)
Input Voltage	DC12V (Adjustable DC24V)
Current	12V/500mA(±10%);24V/250mA(±10%)
LED	Red shows locked ;Green shows unlocked
Signal Output	Lock signal(NO/NC/COM)
Time	0/3/6/9sec.
Suitable	Wooden door , Glass door ,Metal door , Fireproof door
Surface Temp	≤+20°C
Operating Temp	-20°C~+55°C(-4—131°F)
Cover Finish	Anodized aluminum
Humidity	0~95%(non-condensing)
Weight	4.5KG

About this item

Inbuilt time delay mode and can set up 0,3,6,9sec .It is suitable for the card reader which is with time delay and LED indicator. Holding force: 1200lbs