

ANSI standard Heavy Duty Electric Strike



Advantage:

- Holding 1000kg.
- Special design, NO/NC Adjustable
- Designed for Metal Frame drill a hole, then install it directly.
- Testing to 500000 cycles.
- High-Temperature Painted, Durable and Beautiful Artical.
- CE Certificate by European Union, MACertificate by China Public Security offic

Technical Parameter

Model.NO	SA-DE138-S
Lock Size	124Lx43.7Wx35H(mm)
Keeper	stainless steel precision casting
Static strength	500kg
Voltage	DC12V (Need Order DC24V)
Current	12V/320mA(±10%);24V/160mA(±10%)
Feature	Fail Safe (Factory default);Fail Secure (Adjustable)
Suitable For	Wooden Door,Metal Door,PVC Door
Signal Output	Door status Output,NO/NC/COM
Surface Temperature	Within + 20°C
Suitable Temperature	-10~+55°C(14-131F)
Operating Humidity	0~95%(non-condensing)
Face plate Housing	Painted Steel
Function	Built-out MOV
Optional Accessories	YS-305、YS-306
Weight	0.38kg

About this item

IT is designed for wooden door, metal door, PVC door and so on. There are a group of lock signal output dry contacts in the lock, they are NO/NC/COM, it is used for remote monitoring the state of the lock is locked or not.