



### Advantage:

- Support real time management monitor by multi users and multi devices
- Working with IP camera to realize network real time monitor and video capture
- Support time attendance and on line guard tour function

### Technical Parameter

Model.NO	SA-E04.NET
User	30000
Event	60000 (485)/50000 (TCP/IP)
Alarm event	60000
Communication	Rs485 or TCP/IP
Communication distance	1200 meters (485)
Card reader	Wiegand protocol
Door open method	Card, Card + PSW, PSW, double card, software, free pass, push button, door timer

### Features

- Standard RS485 or TCP/IP communication
- Big Flash capacity can keep data for 10 years if no power
- All of input interfaces have optocoupler protection and system is more stable
- WEB server is built in access control
- We can manage and real time monitor and no need install software
- Access control's time zone can reach as many as 8 group and each group can have different verifications
- Support multi verifications: Card, card+PSW, PSW, double cards, first card opening, door timer, timed alarm
- Two door and Four door controller support inter-locking function
- Support remotely open or close door, alarm, fire alarm
- Support software or manage door through WEB and realize global anti passback
- Support alarm output of multi events like invalid card and time, door alarm, door open overtime
- All of wiegand interfaces are compatible with wiegand protocol like 26,34,37
- Data automatically sends without limitation of access controller QTY
- Separately set each cards'validity. All of our access controllers support 485, TCP/IP controller's mixing installation.