

Extended Wall Mount Door Holder



SAFE EYE



Advantage:

- Col linear Load Test 50kg–110pounds.
- Dual Voltage 12/24 VDC(Adjustable).
- The Standard Voltage is 24VDC when Finished.
- MOV Provides Reverse Current Protection.
- Low Power,Environmental Protection.
- Anti-Residual Magnetism Design.
- Professional Design, Dual Insulate Housing.
- Automatically close the smoke proof door when fire happens.

Technical Parameter

| | |
|-----------------------|---|
| Model.NO | SA-EX602 |
| Dimensions | L90xW90xH114(mm) |
| Holding Force | 180kg(350Lbs) |
| Voltage | Factory Default : 24VDC, 12VDC(Adjustment) |
| Current Draw | 12V/240mA 24V/120mA |
| Signal Output | NO (Green) /NC (Yellow) /COM(White) YD-602L-S |
| Optional | Manual door release button |
| Suitable for | All Kinds of Single & Double Smokeproof Doors |
| Surface Temp | ≤+20°C |
| Operating Temp | -10~+55°C(14-131F) |
| Suitable Humidity | 0~90%(relative humidity) |
| Finishes for Shell | High Temperature Paint and Environmental Protection Zinc |
| Finishes for Armature | Zinc |
| Weight | 1.6kg |

About this item

The low power consumption, Highlights it more environment friendly and more durable. Professional anti-residual magnetism design ensures highest security. It will release automatically the fire door when fire alarms. It also contains build-out release button for testing and build-in MOV which reverse current protection.