

Fail Secure Electric Bolt W/Cylinder



SAFE EYE



Technical Parameter

Model.NO	SA-FSC600-EB
Lock Body	270Lx30WX48H(mm)
Magnetic Plate	100Lx25Wx2.5H(mm)
Bolt	16(length)*16(diameter)(mm)
Voltage	DC12V
Start Current	1200mA
Standby Current	200mA
LED	Light on indicates unlocked, light off indicates locked
Light on indicates unlocked, light off indicates locked	Wooden door, metal door, fireproof door, glass door
Signal Output	Lock signal NO/NC/COM (need order door signal)
Material	304 stainless steel, wire draw finishing
Induction Distance	Within 8mm
Weight	1.6kg

Advantage:

- Low Temperature, safe & Durable.
- Low Power, Environmental Protection.
- Special photoelectricity control, three steps current application.
- Long Life with 500000 cycles.
- MOV Provides Reverse Current Protection.
- Superior Strength Aluminium Alloy, Solid Stainless-Steel Bolt.
- Door statue signal output contact NC, NO, COM
- Double protection for loading current.
- Auto-relock if no Action within 5 secs.
- Certificate: CE&MA.
- Photoelectricity Control, Low Temperature,
- A: The Low Current is Changed immediately;
- B: When door frame doesn't coincide with door leaf, door leaf against the bolt, then the electric bolt will start the low-power function to bring low temperature.
- C: The Photoelectricity Control Technology, prevent the mechanical defect.

Technical Parameter

is an all-metal construction electric bolt. With European-type cylinder and has both electric control and manual control functions and special latch bolt Design. The special design of all-metal linkage parts results it can bear with the temperature of 60 °C or -40 °C below zero. Special adopts 304 stainless steel Bolt by CNC lathe, can withstand 2000kg holding force