



SAFE EYE

Mini single door magnetic lock with signal output



Advantage:

- Collinear Load Test 60kg,120pounds.
- MOV Provides Reverse Current Protection.
- Anti-Residual Magneism Designed.
- High Strength Material,Anodized Aluminum Housing.
- Design with no Mechanical Bolt.
- Increase the holding Force,Dual Insulative Hosing.
- CE Certificate by European Union,MA Certificate by China Public Security Office.

Technical Parameter

Model.NO	SA-ML60-1DS
Signal output	Lock signal NO/COM (YM-60N-S)
Size	80Lx36.5Wx24.1H(mm)
Armature Plate Dimension	75Lx33Wx10H(mm)
Holding Force	60kg(120Lbs)
Input Voltage	DC12V (Adjustable DC24V)
Current	12V/160mA(±10%);24V/80mA(±10%)
Suitable	File Cabinet ,Display Cabinet
Surface Temp	≤+20°C
Operating Temp	-20°C~+55°C(-4—131°F)
Humidity	0~95%(non-condensing)
Cover Finish	Anodized aluminum
Lock Finish	Zinc
Armature Plate Finish	Zinc
Weight	0.5KG

About this item

IT is a mini single door electric lock, it is designed for showcase, cabinet door and easy to install . The holding force is 120lbs.